Apr. 3, 1973 [45]

ART OF MANUFACTURING DRY WALL TAPING AND FINISHING COMPOUNDS WITH A NITROGENOUS-MODIFIED AMYLACEOUS BINDER

[75] Inventor: Robert G. Cummisford, Brookfield,

Wis.

[73] Assignee: Krause Milling Company, Milwau-

kee, Wis.

May 27, 1971 [22] Filed:

[21] Appl. No.: 147,644

Cummisford

[52] U.S. Cl......260/17.4 ST, 106/210, 106/214

[51] Int. Cl.C08b 25/02, C08d 9/06

[58] Field of Search......260/17.4 ST, 17.3; 106/210,

106/214; 52/344

References Cited [56]

UNITED STATES PATENTS

3 270 934	10/1966	Schuttner	106/214
3,411,926	11/1968	Gogek et al	106/210
3,485,776	12/1969	Bruner et al	260/17.3

Primary Examiner-Harold D. Anderson Assistant Examiner—Edward Woodberry Attorney-Morsell & Morsell

ABSTRACT [57]

Urea is combined with a gelatinized amylaceous material using water in an amount less than 20 percent of the total mix, and the mixture is subsequently heated to obtain a binder for use in a dry wall finishing compound.

19 Claims, No Drawings